

**HPS Trailer Pag
for**

EAST

UserID: CJuska_Job_1_of_1

Printer: cp3_11c17_gbflptr

Summary

Document	Pages	Printed	Missed	Copies
WO009823445	21	21	0	1
Total (1)	21	21	0	-

CJuska_Job_1_of_1

Printed by HPS Server
for

EAST

Printer: cp3_11c17_gbflptr

Date: 04/18/03

Time: 14:24:53

Document Listing

Document	Selected Pages	Page Range	Copies
WO009823445	21	1 - 21	1
Total (1)	21	-	-

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B32B 31/06, 3/02	A1	(11) International Publication Number: WO 98/23445 (43) International Publication Date: 4 June 1998 (04.06.98)
<p>(21) International Application Number: PCT/US97/21839</p> <p>(22) International Filing Date: 26 November 1997 (26.11.97)</p> <p>(30) Priority Data: 08/756,983 26 November 1996 (26.11.96) US</p> <p>(71) Applicant: K2, INCORPORATED [US/US]; 300 West Beecher Road, P.O. Box 10, Adrian, MI 49221 (US).</p> <p>(72) Inventor: GERRY, Stephen, W.; 168 Azalea Point Drive South, Ponte Vedra Beach, FL 32082 (US).</p> <p>(74) Agent: FRASER, Donald, R.; Law Offices of MacMillan, Sobanski & Todd, 132C West Second Street, Perrysburg, OH 43551 (US).</p>		<p>(81) Designated States: AU, BR, CA, CN, IL, JP, KR, MX, RU, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report.</i></p>
<p>(54) Title: TUFTED CARPET AND PROCESS FOR PREPARING SAME</p> <div data-bbox="267 1123 1226 1596"></div> <p>(57) Abstract</p> <p>A tufted carpet (10) comprises consecutively a primary backing (12), stitched with loops of yarn (14) to form a tufted structure projecting outwardly from the primary backing (12), a polyolefin locking layer (16), a moisture barrier polyolefin layer (18), and a secondary backing (20) comprising a woven polyolefin.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

TITLE

TUFTED CARPET AND PROCESS FOR PREPARING SAME

FIELD OF THE INVENTION

5 The present invention relates generally to a tufted carpet and a process for preparing same. More particularly, the invention is directed to a tufted carpet including, inter alia, a moisture barrier layer, and to a process for assembling various carpet
10 components and laminating same to prepare a tufted carpet.

BACKGROUND OF THE INVENTION

 It is well-known to prepare tufted carpet by
15 stitching a primary backing material with yarn in such a manner so as to form on the top surface of the backing material a pile comprising numerous closely spaced erect loops of yarn. Typically, the bottom surface of the primary backing material is thereafter coated with a
20 polymeric adhesive and a secondary backing material is adhered thereto. Finally, the assembled structure is passed through an oven and a compression zone to cure the polymeric adhesive and laminate the assemblage into a monolithic tufted carpet structure. By this process,
25 the yarn tufts are banded to the primary backing material, and the secondary backing material is simultaneously banded to the tufted carpet structure.

 While the production process of the prior art includes the insertion of a cured polymeric layer, many

of the tufted carpet structures produced by this well-known process do not contain an effective moisture barrier because of inconsistencies in the application of the polymeric adhesive layer, the variableness of the heating and curing process, and the like.

U.S. Patent No. 4,153,749 discloses a tufted carpet structure comprising consecutive layers of a tufted primary backing, a latex layer, a layer of an electrically conductive polymer, and a secondary backing. Such an assemblage results in a low static carpet, but does not insure that the tufted carpet will contain an effective moisture barrier.

It would be desirable to prepare a tufted carpet having an improved moisture barrier, by a commercially feasible process.

SUMMARY OF THE INVENTION

Accordant with the present invention there surprisingly has been discovered an improved tufted carpet, comprising:

a primary backing stitched with loops of yarn to form a tufted structure projecting outwardly from said primary backing;

a polyolefin locking layer affixed to the primary backing;

a moisture barrier polyolefin layer affixed to the polyolefin locking layer; and

a secondary backing, comprising a woven polyolefin, affixed to the moisture barrier polyolefin layer.

The invention further includes a process for preparing a tufted carpet, comprising the steps of:

providing a primary backing stitched with loops of yarn to form a tufted structure projecting outwardly
5 from said backing;

applying a polyolefin locking layer to the primary backing;

laminating together the primary backing and polyolefin locking layer, to affix the polyolefin
10 locking layer to the primary backing and simultaneously lock the loops of yarn in the primary backing;

providing a secondary backing, comprising a woven polyolefin;

applying a moisture barrier polyolefin layer to the
15 polyolefin locking layer;

contacting the moisture barrier polyolefin layer to the polyolefin locking layer; and

laminating together the primary backing, polyolefin locking layer, moisture barrier polyolefin layer, and
20 secondary backing.

The tufted carpet according to the present invention, as well as the process for making same, is particularly well suited for producing carpeting for use in commercial and residential buildings, motor vehicles,
25 and the like.

BRIEF DESCRIPTION OF THE DRAWING

The novel features that are considered characteristic of the invention are set forth with

particularity in the appended claims. The invention itself, however, will best be understood from the accompanying description of specific embodiments, when read in conjunction with the attendant drawing, in which:

The FIGURE is a side elevational view of an embodiment of a tufted carpet according to the present invention.

10 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the Figure, there is shown generally at 10 a schematic, side elevational view of an embodiment of a tufted carpet according to the present invention. The tufted carpet comprises a primary
15 backing 12 stitched with loops of yarn 14 to form a tufted structure projecting from the primary backing 12. A polyolefin locking layer 16 is affixed to the underside of the primary backing 12 which effectively locks the loops of yarn 14 thereto. A layer of
20 polyolefin 18 is affixed to the polyolefin locking layer 16, which layer 18 effectively provides a moisture barrier for the tufted carpet 10. A secondary backing 20 is affixed to the moisture barrier polyolefin layer 18. The secondary backing 10 provides dimensional
25 stability and rigidity to the tufted carpet 10, thereby facilitating the handleability of same.

The primary backing which is stitched with the pile yarn can be any sheet material conventionally used as the primary backing of a tufted carpet. Useful primary

backing materials include, but are not necessarily limited to, woven jute, woven cotton fabric, woven and non-woven fabrics made from synthetic fibers such as, for example, polypropylene, polyethylene, polyamide, polyester, a rayon, and the like, as well as blends, combinations, and copolymers thereof.

Tufting is conventionally accomplished by inserting reciprocating needles threaded with yarn into the primary backing to form tufts or loops of yarn which project outwardly from one of the major surfaces of the primary backing. Useful materials from which the loops of yarn may be prepared include, but are not necessarily limited to, polyester, polyamide, polypropylene, polyethylene, polyurethane, polycarbonate, polyacetal, nylon, and the like, as well as blends, combinations, and copolymers thereof.

Primary backing materials stitched with loops of yarn to form a tufted structure projecting outwardly from one of the major surfaces thereof which are useful for manufacturing multilayered carpet structures are commercially available and well-known in the art. A preferred primary backing containing tufts of yarn may be obtained from Mohawk Industries, Inc. under the product designation Bigelow.

The polyolefin locking layer according to the present invention may be prepared from polyolefins selected from, but not necessarily limited to, high, medium, or low density polyethylene, polypropylene, polybutylene, and the like, as well as blends and

copolymers thereof. A preferred polyolefin is linear low density polyethylene. The polyolefin locking layer may have a thickness ranging from about 0.1 inch to about 0.4 inch, and may either be clear or pigmented. A
5 preferred linear low density polyethylene, from which the polyolefin locking layer may be extrusion coated onto the primary backing, may be obtained from Chevron Corporation under the product designation #1017.

The moisture barrier polyolefin layer according to
10 the present invention may be prepared from any of the polyolefins listed above as useful for preparing the polyolefin locking layer. The polyolefin used for the moisture barrier polyolefin layer may be the same or different from the polyolefin used for the polyolefin
15 locking layer. A preferred polyolefin for making the moisture barrier polyolefin layer is linear low density polyethylene. The moisture barrier polyolefin layer may have a thickness ranging from about 0.001 inch to about 0.4 inch, and may either be clear or pigmented. A
20 preferred linear low density polyethylene from which the moisture barrier polyolefin layer may be extrusion coated, may be obtained from Chevron Corporation under the product designation #1017.

The secondary backing according to the present
25 invention comprises a polyolefin film including reinforcing filaments. Examples of useful polyolefin materials include, but are not necessarily limited to, high, medium, and low density polyethylene, polypropylene, polybutylene, and the like, as well as

blends and copolymers thereof. A preferred polyolefin is high density polyethylene. The reinforcing filaments may comprise conventional materials such as, for example, glass or metal fibers, or polymeric fibers made from polyester, acrylic polycarbonate, and the like, as well as blends, combinations, and copolymers thereof. The reinforcing filaments are present in the woven polyolefin fabric in a concentration from about a 4 x 2 to about a 24 x 24 tape count per inch. A preferred woven polyolefin may be obtained from Amoco Fabric & Fibers Division under the product designation Style #3824.

The present invention moreover contemplates a method for preparing a tufted carpet. A primary backing stitched with loops of yarn to form a tufted structure projecting outwardly from the primary backing is provided. A polyolefin locking layer is applied to the primary backing. The primary backing and polyolefin locking layer are laminated together, to affix the polyolefin locking layer to the primary backing and lock the loops of yarn to the primary backing. A secondary backing is provided, and a moisture barrier polyolefin layer is applied to a surface thereof. The moisture barrier polyolefin layer is contacted to the polyolefin locking layer, and the entire assemblage is laminated together. Thus, a tufted carpet having a pin-hole-free polyolefin moisture barrier is prepared.

In operation, the polyolefin locking layer is applied to the primary backing by conventional means such as, for example, extrusion coating, roll coating, spraying, dipping, doctor blading, contacting the primary backing with a sheet of polyolefin, etc. Preferably, the polyolefin locking layer is applied by the well-known extrusion coating process. Generally, the extrusion coating die is maintained at a temperature from about 400°F to about 700°F, depending upon the polyolefin utilized, the thickness of the layer of polyolefin desired, the rate of advance of the primary backing web, etc. Preferably, the extrusion temperature ranges from about 580°F to about 625°F. The polyolefin locking layer is applied to a thickness from about 0.1 to about 0.4 inch.

The primary backing and polyolefin locking layer are laminated together utilizing heat and pressure in a conventional laminating apparatus. Lamination may be accomplished by passing the laminae between heated rolls or through a heated belt press. Optionally, the laminae may be preheated by conventional means such as, for example, gas fired or electrical resistance heating ovens, and thereafter passed through conventional compression apparatus such as, for example, a series of driven rolls. Typical lamination pressures generally range from about 10 pounds per linear inch to about 200 pounds per linear inch, while laminating temperatures typically range up to about 350°F. This step effectively affixes the polyolefin locking layer to the

primary backing and simultaneously locks the loops of yarn to the primary backing. Methods and apparatus for laminating plies of materials together are well-known in the art.

5 The moisture barrier polyolefin layer is applied to the secondary backing by any conventional method such as those listed hereinabove. This causes the moisture barrier polyolefin layer to become affixed to the secondary backing. Preferably, the moisture barrier
10 polyolefin layer is extrusion coated onto the secondary backing. Convenient extrusion coating temperatures may range from 400°F to about 700°F. Preferably, the temperature ranges from about 580°F to about 625°F.

 While the moisture barrier polyolefin layer is
15 still at least partially molten, as applied from the extrusion coating die, it is contacted to the polyolefin locking layer. Thus, the moisture barrier polyolefin layer is adhered and becomes affixed to the polyolefin locking layer. Moreover, while the moisture barrier
20 polyolefin layer is still hot, the entire assemblage, comprising the primary backing, polyolefin locking layer, moisture barrier polyolefin layer, and secondary backing, is laminated together to form the tufted carpet structure according to the present invention. The
25 lamination pressure may range from about 10 pounds per linear inch to about 200 pounds per linear inch.

 In the case where the application of the moisture barrier polyolefin layer to the secondary backing does not result in a molten moisture barrier polyolefin

layer, the moisture barrier polyolefin layer is contacted to the polyolefin locking layer and the entire assemblage, comprising the primary backing, polyolefin locking layer, moisture barrier polyolefin layer, and
5 secondary backing, is passed through a heated laminating station or is preheated and passed through a conventional lamination (compression) station at the pressures and temperatures set forth above.

Thus, the moisture barrier polyolefin layer is
10 affixed to the polyolefin locking layer, forming the tufted carpet according to the present invention.

It must be noted that the disclosed process conditions and materials are not sharply critical for the successful preparation of a tufted carpet structure,
15 according to the present invention. The process conditions and materials of construction described hereinabove are generally disclosed in terms which are conventional in the art to the practice of this invention. Occasionally, however, the process
20 conditions and materials as described may not be precisely applicable for each structure included within the disclosed scope.

Those instances where this occurs will be readily recognizable by those ordinarily skilled in the art. In
25 all such cases, either the process or materials may be modified in a conventional manner known to those ordinarily skilled in the art, e.g., by increasing or decreasing lamination temperatures and/or pressures, by varying the thicknesses of various laminae, by routine

substitutions of operable materials, etc., or other process conditions or materials which are otherwise conventional will be applicable to the present invention.

5 From the foregoing description, one ordinarily skilled in the art can easily ascertain the essential characteristics of this invention and, without departing from its spirit and scope, can make various changes and modifications to adapt the invention to various uses and
10 conditions.

WHAT IS CLAIMED IS:

1. A tufted carpet, comprising:

5 a primary backing stitched with loops of yarn to form a tufted structure projecting outwardly from said primary backing;

a polyolefin locking layer affixed to the primary
10 backing;

a moisture barrier polyolefin layer affixed to the polyolefin locking layer; and

15 a secondary backing, comprising a woven polyolefin, affixed to the moisture barrier polyolefin layer.

2. The tufted carpet according to Claim 1, wherein the primary backing is prepared from jute,
20 cotton, or synthetic fibers selected from polypropylene, polyethylene, polyamide, polyester, and rayon, as well as blends, combinations, and copolymers thereof.

3. The tufted carpet according to Claim 1,
25 wherein the loops of yarn are prepared from polyester, polyamide, polypropylene, polyethylene, polyurethane, polycarbonate, polyacetal, and nylon, as well as blends, combinations, and copolymers thereof.

4. The tufted carpet according to Claim 1,
wherein the polyolefin locking layer is selected from
high, medium, and low density polyethylene,
5 polypropylene, and polybutylene, as well as blends and
copolymers thereof.

5. The tufted carpet according to Claim 4,
wherein the polyolefin is low density polyethylene.

10

6. The tufted carpet according to Claim 1,
wherein the polyolefin locking layer ranges in thickness
from about 0.1 inch to about 0.4 inch.

15 7. The tufted carpet according to Claim 1,
wherein the moisture barrier polyolefin layer is
selected from high, medium, and low density
polyethylene, polypropylene, and polybutylene, as well
as blends and copolymers thereof.

20

8. The tufted carpet according to Claim 7,
wherein the polyolefin is low density polyethylene.

9. The tufted carpet according to Claim 1,
25 wherein the moisture barrier polyolefin layer ranges in
thickness from about 0.001 inch to about 0.4 inch.

10. The tufted carpet according to Claim 1,
wherein the secondary backing comprises a polyolefin
film selected from high, medium, and low density
polyethylene, polypropylene, and polybutylene, as well
5 as blends and copolymers thereof.

11. The tufted carpet according to Claim 1,
wherein the secondary backing comprises reinforcing
fibers selected from glass, metal, polyester, acrylic
10 and polycarbonate fibers, as well as blends,
combinations, and copolymers thereof.

12. The tufted carpet according to Claim 1,
wherein the secondary backing reinforcing fibers are
15 present in a concentration from about 4 x 2 to about 24
x 24 tape count per inch.

13. A process for preparing a tufted carpet,
comprising the steps of:

5 providing a primary backing stitched with loops of
yarn to form a tufted structure projecting outwardly
from said primary backing;

10 applying a polyolefin locking layer to the primary
backing;

15 laminating together the primary backing and
polyolefin locking layer, to affix the polyolefin
locking layer to the primary backing and simultaneously
lock the loops of yarn in the primary backing;

providing a secondary backing, comprising a woven
polyolefin;

20 applying a moisture barrier polyolefin layer to the
polyolefin locking layer;

contacting the moisture barrier polyolefin layer to
the polyolefin locking layer; and

25 laminating together the primary backing, polyolefin
locking layer, moisture barrier polyolefin layer, and
secondary backing.

14. The process for preparing a tufted carpet according to Claim 13, wherein the polyolefin locking layer is applied to the primary backing by extrusion coating.

5

15. The process for preparing a tufted carpet according to Claim 14, wherein the extrusion temperature ranges from about 400°F to about 700°F.

10

16. The process for preparing a tufted carpet according to Claim 13, wherein the primary backing and polyolefin locking layer are laminated together at a pressure ranging from about 10 pounds per linear inch to about 200 pounds per linear inch.

15

17. The process for preparing a tufted carpet according to Claim 13, wherein the primary backing and polyolefin backing layer are laminated together at a temperature up to about 350°F.

20

18. The process for preparing a tufted carpet according to Claim 13, wherein the moisture barrier polyolefin layer is applied to the secondary backing by extrusion coating.


25

19. The process for preparing a tufted carpet according to Claim 18, wherein the extrusion temperature ranges from about 400°F to about 700°F.

20. The process for preparing a tufted carpet according to Claim 18, wherein the moisture barrier polyolefin layer is contacted to the polyolefin locking layer while the moisture barrier polyolefin layer is at least partially molten.

21. The process for preparing a tufted carpet according to Claim 20 wherein the primary backing, polyolefin locking layer, moisture barrier polyolefin layer, and secondary backing are laminated together at a pressure from about 10 pounds per linear inch to about 200 pounds per linear inch.

22. The process for preparing a tufted carpet according to Claim 13, wherein the primary backing, polyolefin locking layer, moisture barrier polyolefin layer, and secondary backing are laminated together at a pressure from about 10 pounds per linear inch to about 200 pounds per linear inch and at a temperature up to about 350°F.



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US97/21839

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :B32B 31/06, 3/02

US CL :428/95; 156/72

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 428/95; 156/72

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4,844,765 A (REITH) 04 July 1989, see entire document.	1-22

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
B earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
30 JANUARY 1998

Date of mailing of the international search report
25 FEB 1998

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231
Facsimile No. (703) 305-3230

Authorized officer

TERREL MORRIS

Telephone No. (703) 308-2351